

STOCK VACUUM HOSE

Hose type	Hose	Description	Temp °F	Flexibility	1 1/2" Hose Weight	Stock Lengths
	Diameters				oz/foot	(Feet)
I	1 1/2" , 2"	Medium duty, crushproof hose provides good chemical, abrasion, kink and UV resistance.	-40 to +140	Flexible	4.1	25, 50
N	1 1/2" , 2"	Medium industrial duty PVC hose with vinyl coated spring steel.	-10 to +160	Very Flexible	3.7	25, 50
RSC	1 1/2" , 2"	Static conductive polyethylene crushproof hose with carbon black for permanent static conductivity. Surface resistivity of 10 ³ to 10 ⁵ ohms per square.	-40 to +140	Flexible	4.3	25, 50
S	1 1/2" , 2"	Static dissipative polyurethane hose reinforced with an external ABS helix and internal embedded copper grounding wire. Surface resistivity of 10 ⁸ to 10 ¹⁰ ohms per square conductivity and flexibility.	-40 to +200	Very Flexible	3.9	25, 50

Hoses are available with and without hose cuffs. For additional lengths, diameters and hose types please call.

VACUUM AND DUST HOSE SELECTION CHART

Hose Type	I	N	RSC	S
Dry	X	X	X	X
Wet	X	X	X	
Asbestos Removal	X	X	X	X
Carpet Extraction Portable	X	X		
Clean Room	X	X		
Concrete Dust	X			X
Industrial Central Vacuums	X	X	X	X
Lead Paint Dust	X	X	X	X
Light Weight		X		
Marine Duty	X			
Oil Resistance		X		
Power Tools Portable	X	X		
Static Conductive			X	X
Vacuum Commercial Portable	X	X		X
Vacuum Industrial Portable	X	X	X	X
Vacuum Shop Type	X	X		X
Woodworking	X	X		X
Temp Range	-40 +140	-10 +160	-40 +140	-40 +200

See our complete line of D-Lead[®] cleaning solutions at www.esca-tech.com



3747 N. Booth Street
Phone: (414) 962-5323

Milwaukee, WI 53212
Fax: (414) 962-7003

www.esca-tech.com